

## **Master Scales**

## **Digital Portion Control Scale, 5 lb**

## Model: SD0502

This exclusive NSF® Certified scale was designed for demanding foodservice kitchens. It features tare, hold and field calibration to ensure accuracy over time. Small profile and BioCote® antimicrobial technology. Batteries and power adapter included.



| Features                 | Small profile, selectable units, tare function, hold, field calibration, overload indication, battery status indication, removable stainless steel platform, on/off button, AC adapter |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Measurement Range        | 5 lb/2.27 kg capacity                                                                                                                                                                  |
| Unit of Measure          | lb:oz/kg.g                                                                                                                                                                             |
| Resolution               | 0.1 oz, 1 g                                                                                                                                                                            |
| Accuracy                 | 1 kg ±3g; 2 kg ±6g                                                                                                                                                                     |
| Tare                     | Tare function                                                                                                                                                                          |
| Calibration              | Field calibration                                                                                                                                                                      |
| Water Resilience         | IP54: protected from water splashes from any direction for 10 minutes; dust protected                                                                                                  |
| Response Time            | 0.125 second response                                                                                                                                                                  |
| On/Off                   | On/off button                                                                                                                                                                          |
| Auto-off                 | Auto-off after 2 minutes; disabled when the AC adapter is used                                                                                                                         |
| Housing Material         | Food-safe ABS plastic                                                                                                                                                                  |
| Display Material         | LCD                                                                                                                                                                                    |
| Display Size             | 3.35 W x 0.866 H (in)/8.5 W x 2.2 H (cm)                                                                                                                                               |
| Load Cell                | Single point load cell                                                                                                                                                                 |
| Platform Material        | 304 stainless steel                                                                                                                                                                    |
| Platform Size            | 5.35 W x 5.35 L (in)/13.6 W x 13.6 L (cm), removable                                                                                                                                   |
| Operating Range          | 32 to 104°F/0 to 40°C ≤90% RH                                                                                                                                                          |
| Power                    | AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (500mA) output                                                                                                                           |
| Battery                  | Two AAA alkaline batteries (WERCSmart) included                                                                                                                                        |
| Battery Life             | 2 years (3 times/day, 30 s/time)                                                                                                                                                       |
| Dimensions               | 5.90 W x 1.75 H x 7.87 D (in)/15.0 W x 4.45 H x 20.0 D (cm)                                                                                                                            |
| Weight                   | 18.5 oz / 524 g (including battery)                                                                                                                                                    |
| UPC                      | 0 18436 00818 7                                                                                                                                                                        |
| Certification            | NSF® Certified, WEEE, CE                                                                                                                                                               |
| Antimicrobial Protection | BioCote®                                                                                                                                                                               |
| Warranty                 | 1-Year Limited Warranty                                                                                                                                                                |
| Optional Accessories     | 2 kg calibration weight (WT02), 500 g calibration weight (WT500), Small Profile Platform (AD-PF0502), Power Adapter (AD-AC3302)                                                        |
| Replacement Parts        | Small Profile Platform (AD-PF0502), Power Adapter (AD-AC3302)                                                                                                                          |
|                          |                                                                                                                                                                                        |



© 04-2022 CDN CD2921100 - 4/22

**Tel** 800 338-5594 **Fax** 800 879-2364 **Web** CDNmeasurement.com